



Alliant Approved AMP combination CT products can now be installed in either Pad Mounted or Wall Mounted Applications



MCT = Combined Main Disconnect & CT

- 400-1200AMP 240 and 600 volt, 3 phase 4 wire and 1 phase 3 wire. NEMA 1/3R dual rated and ISC ratings of 85KA RMS symmetrical with no cable lashing required.
- All cabinets combine both the CT compartments and main disconnect in one enclosure.
- MCT is UL listed and labeled, suitable for service entrance equipment. Cabinets meet all NEMA and NEC code standards.
- Wiring: Line is at the top or bottom and load is always on the opposite end. Welded enclosure incorporates an internal wireway to accommodate top or bottom entry and exit for either line or load conduits.



SCT = Combined 6 disconnects & CT

- 400-1200AMP 240 and 600 volt, 3 phase 4 wire and 1 phase 3 wire. NEMA 1/3R dual rated and ISC ratings of 85KA RMS symmetrical with no cable lashing required.
- All cabinets are surface mounted and suitable for indoor or outdoor applications.
- Both doors supplied with 3 point pad lockable handles.
- UL listed and labeled. Cabinets meet all NEMA and NEC code standards.
- All cabinets combine CT compartment with a 6 disconnect panel in one enclosure.

For more information, please contact your AMP sales representative